

PS-6616AFHD2

1 SATA 5 in 1 DVR 4MN Series**Parameters:****Features:**

- Support 16ch 4M-N non real-time encoding;
- Support AHD, TVI, CVI, CVBS, IP video input;
- HDMI/VGA simultaneous video output;
- 1.5U Case, 2 SATA (Up to 8TB);
- 1*10/100Mbps auto-sensing Ethernet port, RJ45 port;
- Automatic networking support, a key to add equipment;
- Support the Onvif protocol;
- Support GB28181 (Optional);
- Cloud services, P2P, alarm information push to phone;
- Support remote access, support ARSP;
- Support DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP search, Alarm center, etc;
- Mobile phone remote monitoring (iOS, Android);
- Multi browser access (IE, Chrome, Firefox, Safari);
- Support for more than twenty languages;
- Perfect protection circuit, unique triple watchdog function;
- Support WEB, CMS, VMS, Tawai Platform;
- Support coaxial control;
- Support XVI, image quality is better;
- Support intelligent video analysis.

Model:

PS-6616AFHDii

Interface:

	Model	PS-6616AFHD2
System	processor	Hi3521A
Video	Codec	H.264+ (Quasi H.265) /H.264
	Encode	16*4M-N@8fps;8*1080N(5 in 1);16*960H;
	Decode	16*4M-N@6fps;8*1080N(5 in 1);8*960H;
	Multi-mode	Analog: 16*4M-N@8fps;8*1080N;16*960H; Hybrid: 8*1080N@12fps(analog)+8*960P IP: 8*1080P;8*960P;4*5M;4*4M
	Playback	16ch
	Compression	G.711a
Audio	Intercom	Support
	Record mode	Manual>Alarm>Motion detection>Timing
	Inquire mode	Inquire by Time/Calendar/Event/Channel
	Storage mode	HDD Storage, Network Storage
Management	Backup	Network, USB, SATA
	Video input	16*BNC(Support Coaxitron)
	HDMI output	1*HDMI (MAX:1080P)
	VGA output	1*VGA (MAX:1080P)
	Audio I/O	6/1
	Alarm I/O	4/1
	Ethernet port	1*10/100Mbps Ethernet port, RJ45 port
	PTZ control	1*RS485, Support for multiple PTZ protocol
	USB Port	2*USB2.0 ports
Interface	HDD	2*SATA interface (Up to 8TB)
	Temperature	0 °C - + 55 °C
	Humidity	10% -90% RH
	Power supply	12V/4A
	Consumption	<10W(Without HDD)
	Weight	Around 1.8KG
General	Dimension	310mm(L)* 298mm(W)* 60mm(H)