

# PS-1606 TOUCH

## Single door Access Controller

### Single door Access Controller

Single Access Controller that is specialy design for the Office building,Factory employee dormitory,and building commonality passage , offer a access controller solution with simpleness directly and competitive price for consumer

#### Features

- New ultrathin and simple design.
- Standalone, No Control Panels ,single door control.
- Easy and simple to use.
- Design of dustproof and high security.
- Has a flat back so it's easy to install on any flat surface
- Operating Mode: Card only, Keypad only, Card with Keypad or Facility Code only.
- Card capacity is 1600 users.
- Programmable door release time: 1~250 seconds
- Access code can be added or deleted by keypad management.
- Built-in electric buzzer for audible card entry and programming.
- Data is protected even after power failure.
- Machined housing in high durable.
- With hidden code function under keypad only open door mode.
- ISO Mifare one /EM-ID thin card or keyfob optional
- Can be connected with an external reader.tion ( 3 S )



#### Product Feature

Parameter	Model	PS-1606 TOUCH
Display		Red-power pilot, Black-access granted, Yellow-Beep
Keypad		3 x 4 Flat membrane
Power		DC12V 3Amp
Color		Black or ivory-white
Frequency		13.56Mhz or 125khz
Temperature		(-10° C-70° C)
Humidity		10%-90%RH
Dimensions		120(L) x 76(W) x 16(H)MM
Box Dimensions		150(L) x 140(W) x 40(H) MM
Weight		200g
Reading range		Within 10cm
Output format		Wiegand26 bits
External reader		Not support